



I 080 TECHNICAL INFORMATION

AN EASY TO DISPENSE LIQUID SAFE ON FERROUS AND NON-FERROUS METALS LOW USE CONCENTRATION FOR ECONOMY

Product Description:

Mar-Tek I 080 is a low foaming cleaner for aluminum and ferrous metal parts. The superior wetting characteristics allow it to be an exceptional liquid cleaner without the harsh caustic additives.

How and When to Use:

Mar-Tek I 080 should be used 5 to 8 ounces per gallon of water. Operation temperature should be 140 degrees Fahrenheit or more. Cleaning times will vary according to the type and quality of soil being removed.

Product Specifications:

Physical State: Liquid
Odor: Characteristic
Appearance: Clear
pH: 12.3
Solubility in Water: Infinite
Specific Gravity: 1.03
Flash Point: Nonflammable

Packaging:

55 Gallon Poly Drum
5 Gallon Poly Drum

Notes:

Please read and understand the SDS Mar-Tek 1080 sheet for specific health hazard, first aid, and precautionary information before using this product.

Special Features:

Mar-Tek I 080 contains a corrosion preventative to protect the parts washer from corrosion as well as metal part being cleaned from flash rusting, do to rinse.

Precautions Summary:

Mar-Tek I 080 is an eye and skin irritant. Wear protective equipment when handling.

Eyes: Irritating. May injure eye tissue if not removed promptly. Flush eyes with cold water for at least 15 minutes and consult a physician.

Skin: Irritating. May cause damage if not removed promptly. Flush thoroughly with water.

Inhalation: Mists are irritating to eyes and respiratory tract in high concentrations.

Ingestion: Minimal toxicity. May cause throat disorder.

Keep out of reach of children. Do not take internally. For professional use only.